

Cisco TelePresence EX60

Figure 1. Personal TelePresence with Cisco TelePresence EX60



Product Overview

The Cisco TelePresence™ EX60 transforms the workplace by combining work, communications, and collaboration - all on the desktop with just the touch of a finger. Colleagues can instantly work together whether they are separated by a hallway, a street, or several time zones. As part of the EX series, the Cisco TelePresence EX60 supports vivid, lifelike 1080p30 video, natural collaboration, and the simplicity of a touch screen interface for a complete solution that helps ensure conversations are more productive.

The Cisco TelePresence EX60 is an all-in-one tool that streamlines the desktop so you can fluidly move from individual work on your laptop to a quick video call with a colleague, to problem-solving over shared spreadsheets. As an individual contributor or knowledge worker, you can have immediate access to join project meetings or larger team telepresence meetings directly from your desk. With wall-mount capability, the Cisco TelePresence EX60 can be deployed in smaller spaces or shared-space scenarios such as for financial traders, pharmacies, translation services, virtual receptionists, or simply in space-constrained cubicles. With the Cisco TelePresence EX60, the productive power of personal telepresence can be shared throughout the organization.

Total Solution

The Cisco TelePresence EX60 is part of the broad portfolio of Cisco TelePresence systems offering immersive, multipurpose, and personal endpoints to meet the needs of organizations of all sizes. Cisco TelePresence technology powers the new way of working where everyone, everywhere can be more productive through face-to-face collaboration.

Features and Benefits

- Video resolutions of 1080p30 and 720p60 bring the Cisco TelePresence experience to the desk.

- A high-quality 21.5-inch PC screen with clear 1920 x 1080 resolution enables a transparent, one-tool device to work, meet, and collaborate.
- The 8-inch Cisco TelePresence touch screen interface allows for simple control.
- Collaboration is natural with WXGA/720p content sharing, transparent one-touch sharing of high-definition (HD) content, and a built-in document camera feature.
- A Cisco TelePresence PrecisionHD camera enables video clarity and optimal F1.7, 50° field of view.
- H.323 and Session Initiation Protocol (SIP) with bandwidth up to 6 Mbps point-to-point provide the possibility to establish calls with very high quality.
- Dual front speakers provide for superior audio.
- An integrated document camera allows for easy sharing of physical documents and objects with a quick flip of the main camera.
- A wideband handset is included; you also can add a headset input for privacy.
- The system is wall-mountable with select VESA brackets.
- The system is standards-based for immediate connectivity to anyone regardless of system, from PC video to immersive telepresence, to a meeting room around the globe.

Product Specifications

Table 1 lists the physical specifications; Table 2 gives video and audio specifications; and Table 3 gives network, security, and management specifications of the Cisco TelePresence EX60.

Table 1. Product Specifications

Product compatibility	Fully compatible with standards-compliant telepresence and video systems	
Software compatibility	Cisco TelePresence Software Version TC4.0 or later	
Components	Fully integrated unit including: <ul style="list-style-type: none"> • Codec • Display • Camera • Microphone and loudspeakers • Cables including: DVI-I-to-VGA cable, DVI-D cable, 3.5-mm jack audio cable, LAN cable, power adapter, and power cable 	
Display	<ul style="list-style-type: none"> • 21.5-in. LCD monitor (with LED backlight) • Resolution: 1920 x 1080 (16:9) • Contrast ratio: 1000:1 • Viewing angle: 170° • Response time: 5 ms • Brightness: 225cd/m2 	
PC and second-source video input	DVI-I	
Supported PC input resolutions	SVGA (800 x 600) to WUXGA (1920 x 1080)	
Camera	<ul style="list-style-type: none"> • Cisco TelePresence PrecisionHD design • Resolutions: 1080p and 720p at 30 frames per second (fps) • Auto focus • Integrated privacy shutter • Document camera mode 	<ul style="list-style-type: none"> • 1/3-in., 2.1 megapixel CMOS sensor • Horizontal field of view: 50° • Vertical field of view: 29° • Focus distance 0.1-infinity • Multicoated all-glass optics

Audio system	<ul style="list-style-type: none"> • Two stereo front speakers • Integrated full-range microphone • One 3.5-mm line-in jack for PC or other audio source • Two 3.5-mm jack for headset • Wideband handset • Bluetooth-ready 	
User interface	Cisco TelePresence touch screen <ul style="list-style-type: none"> • Eight-inch projected capacitive touch screen • Resolution: 480 x 800 	
Language support	English	
Physical dimensions (H x L x D)	Cisco TelePresence EX60 main unit: 20.0 x 20.5 x 5.4 in. (50.8 x 52 x 13.8 cm)	<ul style="list-style-type: none"> • Cisco TelePresence touch screen: 1.7 x 9.0 x 5.7 in. (4.4 x 22.8 x 14.5 cm) • Cisco TelePresence touch screen with headset: 3.0 x 11.4 x 7.4 in. (4.4 x 22.8 x 14.5 cm) • Cable length: 47 in. (120 cm)
Weight	Cisco TelePresence EX60 main unit: 12.9 lb (5.85 kg)	<ul style="list-style-type: none"> • Cisco TelePresence touch screen: 1.4 lb (0.64). • Cisco TelePresence touch screen with handset: 2.1 lb (0.94 kg)
Power	Autosensing power supply 100-240 VAC, 50/60 Hz 55 watts	
Temperature range	Operating temperature and humidity: <ul style="list-style-type: none"> • Ambient temperature: 32 to 95°F (0 to 35°C) • Relative humidity (RH): 10 to 90% • Storage and transport temperature at RH 10-90% (noncondensing): -4 to 140°F (-20 to 60°C) 	
Approvals and compliance	<ul style="list-style-type: none"> • Directive 2006/95/EC (Low-Voltage Directive) - Standard EN 60950-1 • Directive 2004/108/EC (EMC Directive) - Standard EN 55022, Class A - Standard EN 55024 - Standard EN 61000-3-2/-3-3 • Approved according to UL 60950-1 and CSA 60950-1-07 • Complies with FCC15B Class A 	

Table 2. Video and Audio Specifications

Bandwidth	H.323/SIP up to 6 Mbps point-to-point	
Video standards	<ul style="list-style-type: none"> • H.261 • H.263 • H.263+ • H.264 	
Video features	<ul style="list-style-type: none"> • Widescreen: 16:9 • Advanced screen layouts • Intelligent video management • Local auto layout 	
Live video resolutions (encode/decode)	<ul style="list-style-type: none"> • 176 x 144@30 fps (QCIF) • 352 x 288@30 fps (CIF) • 512 x 288@30 fps (w288p) • 576 x 448@30 fps (448p) • 768 x 448@30 fps (w448p) • 704 x 576@30 fps (4CIF) • 1024 x 576@30 fps (w576p) • 640 x 480@30 fps (VGA) • 800 x 600@30 fps (SVGA) • 1024 x 768@30 fps (XGA) • 1280 x 1024@30 fps (SXGA) • 1280 x 720@30 fps (720p30) 	<ul style="list-style-type: none"> • 1280 x 768@30 fps (WXGA) • 1920 x 1080@30 fps (1080p30)[*] • 1440 x 900@30 fps (WXGA+)[*] • 1680 x 1050@30 fps (WSXGA+)[*] • 1600 x 1200@30 fps (UXGA)[*] • 512 x 288@60 fps (w288p60)[*] • 768 x 448@60 fps (w448p60)[*] • 1024x576@60 fps (w576p60)[*] • 280x720@60 fps (720p60) * Requires premium resolution option

Audio standards	<ul style="list-style-type: none"> • G.711 • G.722 • G.722.1 • 64/128 kbps MPEG4 AAC-LD • AAC-LD stereo
Audio features	<ul style="list-style-type: none"> • CD-quality 20-kHz stereo • Acoustic echo canceling • Automatic gain control • Automatic noise reduction • Active lip synchronization
Dual stream	<ul style="list-style-type: none"> • H.239 (H.323) dual stream • BFCP (SIP) dual stream • Support for resolutions up to 1080p30 in both main stream and dual stream simultaneously

Table 3. Network, Security and Management Specifications

Protocols	<ul style="list-style-type: none"> • H.323 • SIP
Network interfaces	<ul style="list-style-type: none"> • Internal 2-port Ethernet switch • One LAN/Ethernet (RJ-45) 10/100/1000 Mbps for PC • One LAN/Ethernet (RJ-45) 10/100/1000 Mbps for LAN
Other interfaces	<ul style="list-style-type: none"> • One USB device for future applications • Bluetooth for future applications
IP network features	<ul style="list-style-type: none"> • Domain Name System (DNS) lookup for service configuration • Differentiated Services (QoS) • IP adaptive bandwidth management (including flow control) • Auto gatekeeper discovery • Dynamic playout and lip-sync buffering • H.245 DTMF tones in H.323 • Date and time support with Network Time Protocol (NTP) • Packet loss-based downspeeding • DNS-based URI dialing • TCP/IP • Dynamic Host Configuration Protocol (DHCP) • IEEE 802.1x network authentication • IEEE 802.1q VLAN
Firewall traversal	<ul style="list-style-type: none"> • Cisco TelePresence Expressway Technology • H.460.18 and H.460.19 Firewall Traversal
Embedded encryption	<ul style="list-style-type: none"> • H.323/SIP point-to-point • Standards-based: H.235 v2 and v3 and Advanced Encryption Standard (AES) • Automatic key generation and exchange • Supported in dual stream
Security features	<ul style="list-style-type: none"> • Management via Secure HTTP (HTTPS) and Secure Shell (SSH) Protocol • IP administration password • Menu administration password • Disable IP services • Network settings protection
System management	<ul style="list-style-type: none"> • Support for the Cisco TelePresence Management Suite • Total management through embedded Simple Network Management Protocol (SNMP), Telnet, SSH, XML, and Simple Object Access Protocol (SOAP) • Remote software upload: Through web server, Secure Copy Protocol, HTTP, and HTTPS

Directory services	<ul style="list-style-type: none"> • Support for local directories (My Contacts) • Corporate directory • Unlimited entries using server directory supporting • Lightweight Directory Access Protocol (LDAP) and H.350 • Unlimited number for corporate directory (available with Cisco TelePresence Management Suite (TMS)) • Local directory: 200 numbers • Received calls • Placed calls • Missed calls with date and time
---------------------------	---

Ordering Information

To place an order, please contact your Cisco Representative.

Table 4. Ordering Information

Product Name	Part Number
Cisco TelePresence EX60	119300
Premium Resolution Option	140142PR

Cisco Service and Support

Cisco and our partners provide a broad portfolio of smart, personalized services and support that can help you realize the full business value of your Cisco TelePresence investment by increasing business agility and network availability. This portfolio of services accelerates business innovation by harnessing the network as a powerful business platform. For more information about these services, visit: <http://www.cisco.com/go/telepresenceservices>.

For More Information

For more information about the Cisco TelePresence EX60, visit <http://www.cisco.com/go/telepresence> or contact your local Cisco account representative.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)