

Cisco TelePresence Precision 60 Camera

When you need the best clarity for video conferencing, this camera is the one to use. And the Cisco TelePresence® Precision 60 Camera (Precision 60) not only delivers a premier imaging experience, it also gives you a high level of flexibility for easy integration into meeting rooms, boardrooms, and special industry projects (Figure 1).

Precision 60 provides a powerful integrator imaging solution for large meeting room scenarios; the camera has the following capabilities:

- Industry's best image quality, 1080p60, 20x zoom, wide-angle view
- Great adaptability to light conditions; low noise interference for better image
- Large zoom range to cover large and advanced scenarios

Figure 1. Cisco TelePresence Precision 60 Camera



Product Features

Table 1 summarizes the key features for the Precision 60 Camera.

Table 1. Feature Summary

Feature Summary	
Design features	<ul style="list-style-type: none"> • True 1080p60 video • The next-generation HD video collaboration camera • Professional-grade connectors • Unmatched quality and flexibility • Compatible with Cisco TelePresence SX80 Codec

Product Capabilities

Table 2 lists the product capability specifications for the Precision 60 Camera.

Table 2. Product Specifications

Specification	Description
Resolution	<ul style="list-style-type: none">• 1920 x 1080 at 60 fps
Zoom	<ul style="list-style-type: none">• 10x Optical Zoom• 2x Digital Zoom• 20x Total Zoom
Pan and tilt	<ul style="list-style-type: none">• Pan range: +/- 100 degrees• Tilt range: +/- 20 degrees
Field of view (FoV)	<ul style="list-style-type: none">• Horizontal FoV: 80 degrees• Vertical FoV: 48.8 degrees
Focus distance	<ul style="list-style-type: none">• 1.0m to infinity (wide)
F-value	<ul style="list-style-type: none">• 1.5
Camera control	<ul style="list-style-type: none">• Ethernet
Focus, white balance, and brightness	<ul style="list-style-type: none">• Manual or automatic
IP network features	<ul style="list-style-type: none">• DNS lookup for service configuration• Date and Time support via NTP• TCP/IP• DHCP
Network interfaces	<ul style="list-style-type: none">• One LAN/Ethernet (RJ-45) 10/100 Mbit
Video interfaces	<ul style="list-style-type: none">• HDMI 1.4• 3G-SDI
Power	<ul style="list-style-type: none">• 12V/3A• 100-120/200-240 VAC, 50/60 Hz
Operating temperature and humidity	<ul style="list-style-type: none">• 0 to 40°C (32 to 104°F) ambient temperature• 10 to 90% relative humidity (RH)
Storage and transport temperature	<ul style="list-style-type: none">• -20 to 60°C (-4 to 140°F) at RH 10-90% (noncondensing)
Dimensions	<ul style="list-style-type: none">• Length: 10.6 in. (26.8 cm)• Height: 6 in. (15.2 cm)• Depth: 6.4 in. (16.3 cm)• Weight: 5.5 lbs (2.5 kg)

Ordering Information

To place an order, please contact your local Cisco representative and refer to Table 3.

Table 3. Ordering Information

Product Name	Part Number	Compliance Model Number
Cisco TelePresence Precision 60 Camera spare	CTS-CAM-P60=	TTC8-07

Cisco Service and Support

Cisco and our partners provide a broad portfolio of smart, personalized services and support that can help you realize the full business value of your Cisco TelePresence investment by increasing business agility and network availability. This portfolio of services accelerates business innovation by harnessing the network as a powerful business platform. For more information about these services, please visit:

<http://www.cisco.com/go/telepresenceservices>.




Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)